



FAIRCHILD
SEMICONDUCTOR®

QFET™

FQP10N60C/FQPF10N60C

FQP10N60C/FQPF10N60C 600V N-Channel MOSFET


General Description

These N-Channel enhancement mode power field effect transistors are produced using Fairchild's proprietary, planar stripe, DMOS technology.

This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency switched mode power supplies, active power factor correction, electronic lamp ballasts based on half bridge topology.

Features

- 9.5A, 600V, $R_{DS(on)} = 0.73\Omega$ @ $V_{GS} = 10$ V
- Low gate charge (typical 44 nC)
- Low C_{rss} (typical 18 pF)
- Fast switching
- 100% avalanche tested
- Improved dv/dt capability



Absolute Maximum Ratings $T_C = 25^\circ C$ unless otherwise noted

| Symbol | Parameter | FQP10N60C | FQPF10N60C | Units |
|----------------|--|-----------|-------------|---------------|
| V_{DSS} | Drain-Source Voltage | 600 | | V |
| I_D | Drain Current - Continuous ($T_C = 25^\circ C$) | 9.5 | 9.5 * | A |
| | - Continuous ($T_C = 100^\circ C$) | 3.3 | 3.3 * | A |
| I_{DM} | Drain Current - Pulsed | (Note 1) | 38 | * |
| V_{GSS} | Gate-Source Voltage | | ± 30 | V |
| E_{AS} | Single Pulsed Avalanche Energy | (Note 2) | 700 | mJ |
| I_{AR} | Avalanche Current | (Note 1) | 9.5 | A |
| E_{AR} | Repetitive Avalanche Energy | (Note 1) | 15.6 | mJ |
| dv/dt | Peak Diode Recovery dv/dt | (Note 3) | 4.5 | V/ns |
| P_D | Power Dissipation ($T_C = 25^\circ C$) | 156 | 50 | W |
| | - Derate above $25^\circ C$ | 1.25 | 0.4 | W/ $^\circ C$ |
| T_J, T_{STG} | Operating and Storage Temperature Range | | -55 to +150 | $^\circ C$ |
| T_L | Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds | | 300 | $^\circ C$ |

* Drain current limited by maximum junction temperature.

Thermal Characteristics

| Symbol | Parameter | FQP10N60C | FQPF10N60C | Units |
|-----------------|---|-----------|------------|--------------|
| $R_{\theta JC}$ | Thermal Resistance, Junction-to-Case | 0.8 | 2.5 | $^\circ C/W$ |
| $R_{\theta CS}$ | Thermal Resistance, Case-to-Sink Typ. | 0.5 | -- | $^\circ C/W$ |
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient | 62.5 | 62.5 | $^\circ C/W$ |



FQP10N60C/FQPF10N60C

Electrical Characteristics $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Units |
|--|---|---|-----|-----|------|---------------------------|
| Off Characteristics | | | | | | |
| BV_{DSS} | Drain-Source Breakdown Voltage | $V_{\text{GS}} = 0 \text{ V}$, $I_D = 250 \mu\text{A}$ | 600 | -- | -- | V |
| $\Delta \text{BV}_{\text{DSS}} / \Delta T_J$ | Breakdown Voltage Temperature Coefficient | $I_D = 250 \mu\text{A}$, Referenced to 25°C | -- | 0.7 | -- | $\text{V}/^\circ\text{C}$ |
| I_{DSS} | Zero Gate Voltage Drain Current | $V_{\text{DS}} = 600 \text{ V}$, $V_{\text{GS}} = 0 \text{ V}$ | -- | -- | 1 | μA |
| | | $V_{\text{DS}} = 480 \text{ V}$, $T_C = 125^\circ\text{C}$ | -- | -- | 10 | μA |
| I_{GSSF} | Gate-Body Leakage Current, Forward | $V_{\text{GS}} = 30 \text{ V}$, $V_{\text{DS}} = 0 \text{ V}$ | -- | -- | 100 | nA |
| I_{GSSR} | Gate-Body Leakage Current, Reverse | $V_{\text{GS}} = -30 \text{ V}$, $V_{\text{DS}} = 0 \text{ V}$ | -- | -- | -100 | nA |

On Characteristics

| | | | | | | |
|---------------------|-----------------------------------|--|-----|-----|------|----------|
| $V_{\text{GS(th)}}$ | Gate Threshold Voltage | $V_{\text{DS}} = V_{\text{GS}}$, $I_D = 250 \mu\text{A}$ | 2.0 | -- | 4.0 | V |
| $R_{\text{DS(on)}}$ | Static Drain-Source On-Resistance | $V_{\text{GS}} = 10 \text{ V}$, $I_D = 4.75 \text{ A}$ | -- | 0.6 | 0.73 | Ω |
| g_{FS} | Forward Transconductance | $V_{\text{DS}} = 40 \text{ V}$, $I_D = 4.75 \text{ A}$ (Note 4) | -- | 8.0 | -- | S |

Dynamic Characteristics

| | | | | | | |
|------------------|------------------------------|---|----|------|------|----|
| C_{iss} | Input Capacitance | $V_{\text{DS}} = 25 \text{ V}$, $V_{\text{GS}} = 0 \text{ V}$, $f = 1.0 \text{ MHz}$ | -- | 1570 | 2040 | pF |
| C_{oss} | Output Capacitance | | -- | 166 | 215 | pF |
| C_{rss} | Reverse Transfer Capacitance | | -- | 18 | 24 | pF |

Switching Characteristics

| | | | | | | |
|---------------------|---------------------|---|----|------|-----|----|
| $t_{\text{d(on)}}$ | Turn-On Delay Time | $V_{\text{DD}} = 300 \text{ V}$, $I_D = 9.5 \text{ A}$, $R_G = 25 \Omega$ | -- | 23 | 55 | ns |
| t_r | Turn-On Rise Time | | -- | 69 | 150 | ns |
| $t_{\text{d(off)}}$ | Turn-Off Delay Time | | -- | 144 | 300 | ns |
| t_f | Turn-Off Fall Time | | -- | 77 | 165 | ns |
| Q_g | Total Gate Charge | $V_{\text{DS}} = 480 \text{ V}$, $I_D = 9.5 \text{ A}$, $V_{\text{GS}} = 10 \text{ V}$ | -- | 44 | 57 | nC |
| Q_{gs} | Gate-Source Charge | | -- | 6.7 | -- | nC |
| Q_{gd} | Gate-Drain Charge | | -- | 18.5 | -- | nC |

Drain-Source Diode Characteristics and Maximum Ratings

| | | | | | | |
|-----------------|---|--|----|-----|-----|---------------|
| I_S | Maximum Continuous Drain-Source Diode Forward Current | -- | -- | 9.5 | A | |
| I_{SM} | Maximum Pulsed Drain-Source Diode Forward Current | -- | -- | 38 | A | |
| V_{SD} | Drain-Source Diode Forward Voltage | $V_{\text{GS}} = 0 \text{ V}$, $I_S = 9.5 \text{ A}$ | -- | -- | 1.4 | V |
| t_{rr} | Reverse Recovery Time | $V_{\text{GS}} = 0 \text{ V}$, $I_S = 9.5 \text{ A}$, $dI_F / dt = 100 \text{ A}/\mu\text{s}$ | -- | 420 | -- | ns |
| Q_{rr} | Reverse Recovery Charge | (Note 4) | -- | 4.2 | -- | μC |

Notes:

1. Repetitive Rating : Pulse width limited by maximum junction temperature
2. $L = 14.2\text{mH}$, $I_{AS} = 9.5 \text{ A}$, $V_{DD} = 50\text{V}$, $R_G = 25 \Omega$. Starting $T_J = 25^\circ\text{C}$
3. $I_{SD} \leq 9.5 \text{ A}$, $dI/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{\text{DSS}}$, Starting $T_J = 25^\circ\text{C}$
4. Pulse Test : Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$
5. Essentially independent of operating temperature